

Europäisches Patentamt  
European Patent Office  
Offic européen des brevets



(11) **EP 1 122 137 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
08.08.2001 Bulletin 2001/32

(51) Int Cl.7: **B60S 1/34**

(21) Application number: **01102122.7**

(22) Date of filing: **31.01.2001**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:  
• **Ohashi, Yasuo, Jidosha Denki Kogyo K.K.  
Yokohama-city, Kanagawa-Prefecture (JP)**  
• **Fuke, Toshiyuki, Jidosha Denki Kogyo K.K.  
Yokohama-city, Kanagawa-Prefecture (JP)**

(30) Priority: **04.02.2000 JP 2000028004**

(74) Representative:  
**Reinhard - Skuhra - Weise & Partner  
Friedrichstrasse 31  
80801 München (DE)**


(71) Applicant: **JIDOSHA DENKI KOGYO KABUSHIKI  
KAISHA  
Yokohama-city, Kanagawa-prefecture (JP)**

(54) **Wiper pivot**

(57) A wiper pivot for a wiper apparatus of motor vehicles, which is provided with a pivot holder 3 having a shaft-holding portion 3b to rotatably support a pivot shaft 2, and a body-fixing portion 3d to be fixed to the vehicle body and formed in one body of resin together with the

shaft-holding portion 3b through a connecting portion 3c, and the connecting portion 3c is further provided with a thin-walled destructible portion 4 to be destroyed at the time when impulsive force exceeding the predetermined value is applied on the pivot shaft 2.

**FIG.1**



## Description

### BACKGROUND OF THE INVENTION

#### Field of the Invention

[0001] This invention relates to a wiper pivot for rotatably supporting a pivot shaft connected with a wiper arm in order to wipe the windshield of the motor vehicle by using the wiper motor.

#### Description of the Prior Art

[0002] As the wiper pivot for supporting rotatably the pivot shaft connected with the wiper arm, a wiper pivot to be used in the wiper linkage 50 shown in FIG.8 has been known. A pair of wiper pivots 51 and 52 are used in the wiper linkage 50 shown in FIG.8, and the first and second wiper pivots 51 and 52 are secured at the both ends of a pipe frame 55, respectively. The first and second wiper pivots 51 and 52 are respectively formed with a first and a second pivot holder 51a and 52a for rotatably supporting a first and a second pivot shaft 53 and 54 respectively and body-fixing portions 51b and 52b. The first and second wiper pivots 51 and 52 are fixed by screwing the respective body-fixing portions 51b and 52b on an inner panel disposed on the under side of a cowl top panel (not shown). The top ends of the first and second pivot shafts 53 and 54 are disposed protrudingly from the cowl top panel, and secured respectively with wiper arms fitted with wiper blades. The first and second pivot shafts 53 and 54 are connected to base ends of a first and a second pivot arm 56 and 57 which form a part of linkage 62 at the respective base ends thereof, and a first link connecting rod 58 which forms another part of the linkage 62 is connected between the respective free ends of the first and second pivot arms 56 and 57. Furthermore, one end of a second link connecting rod 59 which forms another part of the linkage 62 is connected to a position near to the free ends of the first pivot arm 56, and another end of the second link connecting rod 59 is connected to the free end of a motor arm 60 which forms the other part of the linkage 62. The motor arm 60 is secured with an output shaft 61a of a wiper motor 61 at the base end thereof.

[0003] In the aforementioned conventional wiper pivot, there is a problem in that an object (body) receives a remarkable impact from the protruding pivot shafts 53 and 54 at the time of collision of the object against the pivot shafts 53 and 54.

### SUMMARY OF THE INVENTION

[0004] It is, therefore, a purpose of the present invention to provide a wiper pivot, which is possible to prevent the object (body) from the large impulsive force even if the pivot shaft collides with the object from the outside.

[0005] The above-mentioned purpose can be

achieved by providing a wiper pivot according to this invention, which is characterized by comprising a pivot shaft provided with a base end connected to a wiper motor through a wiper linkage, and a top end to be disposed protrudingly from a body panel of the vehicle and connected to a wiper arm fitted with a wiper blade; and a pivot holder made of resin and provided with a shaft-holding portion having a shaft hole for rotatably supporting the pivot shaft and a body-fixing portion to be secured on the body panel of the vehicle, formed in one body together with the shaft-holding portion through a connecting portion; wherein the connecting portion of the pivot holder is provided with a thin-walled destructible portion to be destroyed at the time when impulsive force exceeding a predetermined value is applied on the pivot shaft.

[0006] In the wiper pivot according to this invention, if an object collides with the pivot shaft disposed protrudingly from the vehicle body panel and large impulsive force exceeding the predetermined value is applied to the pivot shaft, the destructible portion of the pivot holder is destroyed, whereby the shaft holding portion and the body-fixing portion of the pivot holder are separated from each other and the pivot holder is displaced in the direction of the vehicle body panel. Therefore, the large impulsive force can not be applied to the object even if the object collides with the pivot shaft.

### BRIEF DESCRIPTION OF THE DRAWINGS

#### [0007]

FIG.1 is a perspective view illustrating an embodiment of the wiper pivot according to this invention; FIG.2 is a side view of the wiper pivot shown in FIG.1; FIG.3 is a top view of the wiper pivot shown in FIG.2; FIG.4 is a bottom view of the wiper pivot shown in FIG.2; FIG.5 is a cross sectional view taken on the lines V-V of FIG.3; FIG.6 is a cross sectional view taken on the lines VI-VI of FIG.3; FIG.7 is a perspective view illustrating the wiper pivot shown in FIG.1 in the state of being mounted on the vehicle body; and FIG.8 is a bottom view of the wiper linkage used in the conventional wiper pivot.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0008] An embodiment of the wiper pivot according to this invention will be described below on basis of FIGS. 1 to 7.

[0009] The wiper pivot 1 shown in figures is composed mainly of a pivot shaft 2, a pivot holder 3 and a destructible portion 4.

**[0010]** The pivot shaft 2 is formed with a pivot arm-fitting portion (not shown) at the base end of a round rod-shaped shaft body 2a. The shaft body 2a of the pivot shaft 2 is formed with a pin-groove 2c at a position near to the top end thereof. A wiper arm-fitting portion 2d is formed at the top end of the shaft body 2a on the upper side of the pin-groove 2c of the pivot shaft 2.

**[0011]** The shaft body 2a of the pivot shaft 2 is inserted rotatably in a shaft hole 3b3 formed in the pivot holder 3. At the pivot arm-fitting portion formed in the base end of the shaft body 2a of the pivot shaft 2 as mentioned above, a pivot arm 5 is secured through a wave washer (not shown) by caulking at a pivot shaft-fixing portion 5a thereof.

**[0012]** A C-shaped pin (stopper) 6 is fitted in the pin-groove 2c of the pivot shaft 2. The outer diameter of the C-shaped pin 6 is larger than the outer diameter of the shaft body 2a of the pivot shaft 2. A plain washer 7 is disposed between the C-shaped pin 6 and a first projection 3b1 of the shaft-holding portion 3b of the pivot holder 3. The inner diameter of the plain washer 7 is slightly larger than the outer diameter of the shaft body 2a of the pivot shaft 2 and the outer diameter of the plain washer 7 is larger than the inner diameter of a shaft hole 3b3 formed in the pivot holder 3. The plain washer 7 is in contact with the first projection 3b1 of the shaft-holding portion 3b. The pivot arm 5 is secured at the base end of the shaft body 2a of the pivot shaft 2 and the C-shaped pin 6 is attached to the pivot shaft 2 through the plain washer 7 at the position near to the top end of the shaft body 2a. Accordingly, the pivot shaft 2 is prevented to come out from the shaft hole 3b3 formed in the shaft-holding portion 3b of the pivot holder 3.

**[0013]** The pivot shaft 2 is formed with a positive screw 2d1 and a serration 2d2 at the wiper arm-fitting portion 2d. The wiper arm-fitting portion 2d of the pivot shaft 2 is passed through a securing portion 20a formed in the base end of a wiper arm 20 shown in FIG. 7, whereby the serration 2d2 of the pivot shaft 2 is engaged with a serration receiver (not shown) formed at the securing portion 20a of the wiper arm 20. The positive screw 2d1 of the pivot shaft 2 is pierced into a hole formed in the securing portion 20a and is screwed into a nut (not shown), thereby securing the wiper arm 20 on the wiper arm-fitting portion 2d of the pivot shaft 2. Furthermore, a wiper blade 21 is fitted to the top end of the wiper arm 20 as shown in FIG. 7.

**[0014]** The pivot arm 2 is disposed so that the wiper arm-fitting portion 2d of the pivot arm 2 may be protruded from a pivot hole 70a formed in a cowl top panel (body panel) 70 shown in FIG. 7. The wiper arm 20 fitted with the wiper blade 21 is secured to the pivot shaft 2. Therefore, if large impulsive force is applied to the wiper blade 21 or the wiper arm 20, the impulsive energy caused by the impulsive force is given to the shaft-holding portion 3b of the pivot holder 3 through the pivot shaft 2, the C-shaped pin 6 and the plain washer 7.

**[0015]** The pivot holder 3 is formed of resin and pro-

vided with a holder body 3a, a connecting portion 3c, a body-fixing portion 3d and a frame-connecting portion 3e in addition to the shaft-holding portion 3b described above in a united one body.

**[0016]** The holder body 3a is formed in a rectangular shape and disposed in the substantially center of the pivot holder 3. The shaft-holding portion 3b is formed in the center of the holder body 3a.

**[0017]** The shaft-holding portion 3b is formed in a hollow cylindrical shape, and formed with the first projection 3b1 protruding on the upper side of the holder body 3a and a second projection 3b2 protruding on the lower side of the holder body 3a.

The first projection 3b1 of the shaft-holding portion 3b is in contact with the plain washer 7 and the second projection 3b2 of the shaft-holding portion 3b is in contact with the wave washer (not shown) as described above.

**[0018]** The shaft-holding portion 3b is formed with the shaft hole 3b3 opened from the first projection 3b1 toward the second projection 3b2, and inserted rotatably with the shaft body 2a of the pivot shaft 2.

**[0019]** The connecting portion 3c is disposed so as to bridge between the holder body 3a and the body-fixing portion 3d on the right side of the holder body 3a shown in FIG. 2. The connecting portion 3c is formed with the destructible portion 4. The destructible portion 4 is composed of a first thin-walled portion 4a, a second thin-walled portion 4b and a third thin-walled portion 4c.

**[0020]** The first thin-walled portion 4a of the destructible portion 4 is disposed in the center of the connecting portion 3c, and formed in a thin-walled shape on the side of a lower face 3c2 of a first hollow 3c3 cut out in a rectangular shape toward the lower face 3c2 from an upper face 3c1 of the connecting portion 3c. The first thin-walled portion 4a has thickness  $t_2$  sufficiently smaller than height  $t_1$  of the connecting portion 3c as shown in FIG. 5. The first thin-walled portion 4a and the first hollow 3c3 are formed in arcuate shapes on the circumference of a circle with a diameter of "r1" about the same center "a", which is also the center of the shaft hole 3b3 of the shaft-holding portion 3b as shown in FIG. 3.

**[0021]** The second thin-walled portion 4b of the destructible portion 4 is disposed on one side of the lateral of the connecting portion 3c, and formed in a thin-walled shape on the side of the upper face 3c1 of a second hollow 3c4 cut out in a rectangular shape toward the upper face 3c1 from the lower face 3c2 of the connecting portion 3c. The second thin-walled portion 4b has thickness  $t_2$  equal to the thickness of the first thin-walled portion 4a and sufficiently smaller than the height  $t_1$  of the connecting portion 3c as shown in FIG. 6. The second thin-walled portion 4b and the second hollow 3c4 are formed in arcuate shapes on the circumference of the circle with the diameter of "r1" about the center "a" of the shaft hole 3b3 of the shaft-holding portion 3b. A partition wall 3c6 is disposed between the first hollow 3c3 and the second hollow 3c4, and the second hollow 3c4 has an opening on the opposite side of that of the first

hollow 3c3.

[0022] The third thin-walled portion 4c of the destructible portion 4 is disposed on the other side of the lateral of the connecting portion 3c so as to form a pair together with the second thin-walled portion 4b. The third thin-walled portion 4c is formed also in a thin-walled shape on the side of the upper face 3c1 of a third hollow 3c5 cut out in a rectangular shape toward the upper face 3c1 from the lower face 3c2 of the connecting portion 3c. The third thin-walled portion 4c is sufficiently small as compared with the height t1 of the connecting portion 3c and has thickness t2 equivalent to the thickness of the first and second thin-walled portions 4a and 4b as shown in FIG.6. The third thin-walled portion 4c and the third hollow 3c5 are formed in arcuate shapes on the circumference of the circle with the diameter of "r1" about the center "a" of the shaft hole 3b3 in the shaft-holding portion 3b. A partition wall 3c7 is disposed between the first hollow 3c3 and the third hollow 3c5 and the third hollow 3c5 is opened on the opposite side of the opening of the first hollow 3c3.

[0023] The second thin-walled portion 4b, the first thin-walled portion 4a and the third thin-walled portion 4c of the destructible portion 4 are disposed continuously in the circumferential direction of the shaft hole 3b3 of the shaft-holding portion 3b between the shaft-holding portion 3b and the body-fixing portion 3d. Therefore, the connecting portion 3c is destroyed by absorbing the striking energy caused by shearing stress, bending stress or torsional stress applied on the shaft-holding portion 3b through the plain washer 7 from the C-shaped pin 6 at the time when the large impulsive force is applied on the wiper blade 21 or the wiper arm 20. Consequently, the shaft-holding portion 3b and the holder body 3a are separated from the body-fixing portion 3d. In this time, the striking energy applied to the shaft-holding portion 3b is uniformly given against the first, second and third thin-walled portions 4a, 4b and 4c, and the striking energy is absorbed infallibly by the destructible portion 4 because the first, second and third thin-walled portions 4a, 4b and 4c are formed in arcuate shapes on the circumference of the circle about the center "a" of the shaft hole 3b3 in the shaft-holding portion 3b.

[0024] The body-fixing portion 3d of the pivot holder 3 is formed continuously from the connecting portion 3c on the right side of the connecting portion 3c in FIG.2. The body-fixing portion 3d is fitted with a shock-absorbable damper 8 made of rubber in a damper-fitting portion 3d1 formed in a forked shape.

[0025] A bolt (not shown) is passed through the damper 8 and screwed into the inner panel such as a dash upper panel disposed on the lower side of the cowl top panel, thereby securing the pivot holder 3 on the vehicle body at the body-fixing portion 3d.

[0026] The frame-connecting portion 3e of the pivot holder 3 is formed continuously from the holder body 3a on the left side of the shaft-holding portion 3b in FIG.2. The frame-connecting portion 3e is formed at the end

55a of the pipe frame 55 (see FIG.8) through the outsert moulding together with the holder body 3a, the shaft-holding portion 3b, the connecting portion 3c and the body-fixing portion 3d. The end 55a of the pipe frame 55 is compressed in a plate-like shape to form a plate portion 55a1, and formed with a round hole 55a2 in the plate portion 55a1. The shaft-holding portion 3b of the pivot holder 3 is moulded so as to locate the shaft hole 3b3 in the hole 55a2 as shown in FIG.5.

[0027] A pair of such the wiper pivots 1 are disposed to the both ends of the wiper frame 55 of the wiper linkage 50 as shown similarly in FIG.8, and mounted on the vehicle body by screwing the body-fixing portions 3d of the respective wiper pivots 1 on the inner panel of the vehicle body, furthermore the wiper arms 20 and the wiper blades 21 are fitted on the respective pivot shafts 2 protruding from the pivot holes 70a of the cowl top panel 70.

[0028] In the wiper pivot 1 structured as mentioned above, if the predetermined large impulsive force is applied to the wiper arm 20, the wiper blade 21 or the pivot shaft 2 by the collision with the object or body, the impulsive force is given to the shaft-holding portion 3b through the plain washer 7 from the C-shaped washer 6 of the pivot shaft 2, whereby the first, second and third thin-walled portions 4a, 4b and 4c of the destructible portion 4 are cut off by the impulsive force and the shaft-holding portion 4b and the holder body 3a are separated from the body-fixing portion 3d. Accordingly, the pivot shaft 2 is dislocated from the predetermined position in the pivot holder 3 and displaced in the lower direction of the cowl top panel, the impulsive force is received by the body panel having a plane portion and elasticity as compared with the pivot shaft 2, and it is possible to reduce the impulsive force applied on the object.

[0029] As mentioned above, in the wiper pivot according to this invention, the destructible portion of the pivot holder is destroyed in the case where the object collides with the pivot shaft disposed protrudingly on the body panel and large impulsive force exceeding the predetermined value is applied on the pivot shaft, whereby the shaft-holding portion is separated from the body-fixing portion of the pivot holder and it is possible to displace the pivot shaft in the direction of the body panel. Accordingly, an excellent effect can be obtained in that the large impulsive force is not applied on the object even if the object collides with the pivot shaft of the wiper pivot from the outside.

## Claims

1. A wiper pivot for a wiper apparatus of motor vehicles, said wiper pivot comprising:

a pivot shaft provided with a base end connected to a wiper motor through a wiper linkage, and a top end to be disposed protrudingly from a

body panel of the vehicle and connected to a wiper arm fitted with a wiper blade; and a pivot holder made of resin and provided with a shaft-holding portion having a shaft hole for rotatably supporting said pivot shaft and a body-fixing portion to be secured on the body panel of the vehicle, formed in one body together with said shaft-holding portion through a connecting portion; wherein said connecting portion of the pivot holder is provided with a thin-walled destructible portion to be destroyed at the time when impulsive force exceeding a predetermined value is applied on the pivot shaft.

2. A wiper pivot as set forth in claim 1, wherein said destructible portion of said connecting portion is so formed as to be destroyed and separates the shaft-holding portion of said pivot holder from said body-fixing portion of the pivot holder by shearing stress, bending stress or torsional stress caused between said shaft-holding portion and said body-fixing portion of said pivot holder.
3. A wiper pivot as set forth in claim 1, wherein said destructible portion of said connecting portion is composed of a first thin-walled portion formed on a face on one side of said connecting portion and a second thin-walled portion formed on a face on another side of said connecting portion of the pivot holder.
4. A wiper pivot as set forth in claim 3, wherein said first and second thin-walled portions are disposed alternately.
5. A wiper pivot as set forth in claim 1, wherein said destructible portion of said connecting portion is composed of a first thin-walled portion formed on a face on one side of said connecting portion and a pair of a second and a third thin-walled portion formed on a face on another side of said connecting portion of the pivot holder.
6. A wiper pivot as set forth in claim 5, wherein said first thin-walled portion of said destructible portion of said connecting portion is formed at the center of said connecting portion and said second and third thin-walled portions of said destructible portion are formed on both sides of said connecting portion of the pivot holder.
7. A wiper pivot as set forth in claim 6, wherein said first, second and third thin-walled portion of said destructible portion of said connecting portion are formed in arcuate shapes having the center identical with that of the shaft hole of said pivot holder.

8. A wiper pivot as set forth in claim 1, wherein said pivot holder is connected with an end of a pipe frame of the wiper linkage at the shaft-holding portion through outsert moulding.
9. A wiper pivot as set forth in claim 8, wherein said pivot shaft is attached with a stopper on the top end of said pivot shaft and the impulsive force applied to said pivot shaft is transmitted to the shaft-holding portion through said stopper.
10. A wiper pivot for a wiper apparatus of motor vehicles, said wiper pivot comprising:

a pivot shaft provided with a base end connected to a wiper motor through a wiper linkage, and a top end to be disposed protrudingly from a body panel of the vehicle and connected to a wiper arm fitted with a wiper blade; and a pivot holder made of resin and provided with a shaft-holding portion having a bearing for rotatably supporting said pivot shaft and a body-fixing portion to be secured on the body panel of the vehicle, formed in one body together with said shaft-holding portion through a connecting portion of said pivot holder; wherein said connecting portion of the pivot holder is consisting of a thin-walled destructible portion to be destroyed at the time when impulsive force exceeding a predetermined value is applied on the pivot shaft.

11. A wiper pivot for a wiper apparatus of motor vehicles, said wiper pivot comprising:

a pivot shaft provided with a base end connected to a wiper motor through a wiper linkage, and a top end to be disposed protrudingly from a body panel of the vehicle and connected to a wiper arm fitted with a wiper blade; a pivot holder made of resin and provided with a shaft-holding portion having a bearing for rotatably supporting said pivot shaft; a body-fixing portion to be secured on the body panel of the vehicle, and a connecting portion being a thin-walled destructible portion formed in one body together with said shaft-holding portion and body-fixing portion; and a stopper disposed on a top end of said pivot shaft; wherein said stopper transmits the impulsive force applied to said pivot shaft to the shaft-holding portion therethrough.

FIG.1




FIG.2

1




FIG.3






FIG.4




FIG.5







FIG.6




**FIG.7**



**FIG.8**  
(PRIOR ART)





(12)

**EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
29.10.2003 Bulletin 2003/44

(51) Int Cl.7: **B60S 1/34**

(43) Date of publication A2:  
**08.08.2001 Bulletin 2001/32**

(21) Application number: 01102122.7

(22) Date of filing: 31.01.2001

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
 MC NL PT SE TR**  
 Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:

- **Ohashi, Yasuo**, Jidosha Denki Kogyo K.K  
Yokohama-city, Kanagawa-Prefecture (JP)
- **Fuke, Toshiyuki**, Jidosha Denki Kogyo K.K  
Yokohama-city, Kanagawa-Prefecture (JP)

(30) Priority: 04.02.2000 JP 2000028004

(74) Representative:  
**Reinhard - Skuhra - Weise & Partner**  
**Friedrichstrasse 31**  
**80801 München (DE)**


(71) Applicant: **JIDOSHA DENKI KOGYO KABUSHIKI KAISHA**  
Yokohama-city, Kanagawa-prefecture (JP)

**(54) Wiper pivot**

(57) A wiper pivot for a wiper apparatus of motor vehicles, which is provided with a pivot holder 3 having a shaft-holding portion 3b to rotatably support a pivot shaft 2, and a body-fixing portion 3d to be fixed to the vehicle body and formed in one body of resin together with the

shaft-holding portion 3b through a connecting portion 3c, and the connecting portion 3c is further provided with a thin-walled destructible portion 4 to be destroyed at the time when impulsive force exceeding the predetermined value is applied on the pivot shaft 2.

**FIG. 1**





European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 01 10 2122

## DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (In I.C.I.7)
Y	DE 199 18 873 A (ASMO CO LTD ; HONDA MOTOR CO LTD (JP)) 28 October 1999 (1999-10-28) * column 1, line 3 - line 7; figures 1,2,6 * * column 2, line 12 - line 24 * * column 3, line 32 - line 53 * * column 6, line 12 - column 8, line 6 * ---	1-3,8-11	B60S1/34
A	DE 198 33 488 A (HONDA MOTOR CO LTD) 28 January 1999 (1999-01-28) * column 1, line 5 - line 9; figures 1-4 * * column 3, line 50 - line 53 * * column 4, line 4 - column 5, line 14 * ---	1-3,5,7-10	
Y	EP 0 852 195 A (VALEO SYSTEMES ESSUYAGE) 8 July 1998 (1998-07-08) * column 2, line 34 - line 37; figures 1-3 * * column 2, line 51 - line 58 * ---	1-3,8-11	
A	WO 96 20101 A (ORTALE ALESSANDRO ; TEVES GMBH ALFRED (DE); SCHAEEL OLIVER (DE)) 4 July 1996 (1996-07-04) * page 11, paragraph 2 - page 12, paragraph 1; figures 1,6 * ---	1-3,5-7,10	TECHNICAL FIELDS SEARCHED (In I.C.I.7) B60S
A	DE 89 13 885 U (INDUSTRIE MAGNETI MARELLI S.R.L.) 18 January 1990 (1990-01-18) * figure 1 * -----	9,11	
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 22 August 2003	Examiner Jazbec. S
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons S : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (03.02) (P4/C01)



**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 10 2122

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

22-08-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19918873 A	28-10-1999	JP 11301420 A	02-11-1999
		JP 3318267 B2	26-08-2002
		JP 2000062578 A	29-02-2000
		JP 3232278 B2	26-11-2001
		JP 2000062576 A	29-02-2000
		JP 3318266 B2	26-08-2002
		JP 2000062577 A	29-02-2000
		DE 19918873 A1	28-10-1999
		US 6317918 B1	20-11-2001
DE 19833488 A	28-01-1999	JP 11034808 A	09-02-1999
		DE 19833488 A1	28-01-1999
		FR 2766442 A1	29-01-1999
		GB 2327598 A ,B	03-02-1999
		TW 401358 B	11-08-2000
		US 6505376 B1	14-01-2003
EP 0852195 A	08-07-1998	FR 2757914 A1	03-07-1998
		DE 69720398 D1	08-05-2003
		EP 0852195 A1	08-07-1998
WO 9620101 A	04-07-1996	DE 4446315 A1	27-06-1996
		DE 59506918 D1	28-10-1999
		WO 9620101 A1	04-07-1996
		EP 0799142 A1	08-10-1997
		ES 2138752 T3	16-01-2000
		JP 10511327 T	04-11-1998
		US 5960512 A	05-10-1999
DE 8913885 U	18-01-1990	IT 214971 Z2	30-07-1990
		DE 8913885 U1	18-01-1990
		ES 1012243 U1	16-07-1990
		FR 2639593 A3	01-06-1990

EPO FORM P0455

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

